

**PURPOSE:**

To define the best practices for implementing and using **Hygenall® ToxOff™**

**POLICY:**

**Hygenall® ToxOff™** should be used to decon all equipment, apparatus, station and PPE.

**GENERAL:**

- Use for On Scene Decon of equipment and PPE.
- Safe to use on SCBA mask and MMR, NFPA 1851 compliant
- Use inside apparatus for general purpose cleaning of all surfaces.
- Use inside station for general purpose cleaning of door handles, counter tops and shower stalls.
- 5 gallon and 55 gallon buckets are available to refill spray bottles and in a concentration for laundry in extractors and washing machines for PPE.
- Can be sprayed directly on equipment and surfaces being cleaned and wiped off with a damp rag, or spray onto damp rag and wipe surfaces to be cleaned.

**USAGE:**

Use to decontaminate Equipment, Apparatus, Station surfaces and PPE.

**1 quart spray bottles**

Spray onto a damp cloth or directly on surface to be cleaned and then wipe off. Following with a damp cloth is recommended but not required. For gross decon on scene spray on turnouts while on air and brush if needed and then rinse off. Use caution to not let contaminants get onto skin by letting water run down the collar. See gross decon video here: <https://www.youtube.com/channel/UC47yqPmaR6VNW6gHCNsQ6tQ>

**5 and 55 Gallon Bucket**

**Surface/Equipment:** Install 5 gallon or 55 gallon pump and use to refill spray bottles.

**Laundry:** Use 5 ounces for light contamination, and up to 10 ounces for heavy contamination. For heavily contaminated laundry, it may be necessary to soak using a mixture of 2 parts ToxOff to 2 parts water. Use brush and lightly to moderately scrub laundry. Due to varying types of laundry machines and extractors, experimentation may be required to establish best quantity to use. Laundry must be rinsed a minimum of 3 times, and if a machine does not have 3 rinse cycles, then run an additional wash cycle with no soap.

**FLOOR CLEANING:**

For light decon and cleaning, use 6 ounces per gallon of water. For heavily contaminated floors use directly on floor with a mop saturated with *ToxOff™*. Test in an inconspicuous area to ensure surface coating compatibility. Use scrub brush or scrub pad if necessary. Rinse surface and repeat if necessary.