

Cutter | GCU 5040 i EVO 3 (excl. battery)

Specifications

article number		158.052.199
model		GCU 5040 i EVO 3 (excl. battery)
short description		Cutter
max. working pressure	psi	10443
max. cutting opening	in	6.7
theoretical cutting force	lbf	171754
protection rate		IP54
sound emission @ 1m/3.25ft	dB(A)	74
sound emission @ 4m/13ft	dB(A)	65
hydraulic oil type		ISO-L HV VG 15/22
NCT		✓
cutter jaw		inclined
weight, ready for use	lb	41.9
temperature range	°F	-4 + 131
weight excl. battery	lb	39.7
dimensions (AxBxC)	in	33.2 x 11.9 x 10.4
EN 13204 compliant		Yes
EN 13204 classification		BC165I-19.0
EN 13204, cutting capacity		1I 2I 3I 4J 5J
NFPA 1936 compliant		Yes
NFPA 1936, cutting capacity		A7 B7 C6 D7 E8

Safety factors / tests

hydraulic safety factor		2:1
endurance test tool		1000 cycles of biting in material that cannot be cut
endurance test dead man's handle		6000 cycles

Standard supplied with

- Carrying handle with integrated LED lighting
- i-Bolt Technology

Required articles

Greenline Battery BPA283	150.005.823
Greenline Battery BPA285	150.006.208
Greenline Battery Charger BCH1	150.182.208
Greenline Battery Charger BCH2	150.182.209
Greenline Battery Charger BCH3	150.182.286

Accessories

Mains Power Connector BMC1	150.182.206
Mains Power Connector BMC2	150.182.207
Carrying Strap	150.182.249
Battery Pouch	150.182.214

