

## Cutter | GCU 5030 i CL EVO 3 (excl. battery)

### Specifications

article number	158.052.197	
model	GCU 5030 i CL EVO 3 (excl. battery)	
short description	Cutter	
max. working pressure	psi	10443
max. cutting opening	in	6.7
theoretical cutting force	lbf	123420
protection rate	IP54	
sound emission @ 1m/3.25ft	dB(A)	74
sound emission @ 4m/13ft	dB(A)	65
hydraulic oil type	ISO-L HV VG 15/22	
NCT	✓	
cutter jaw	inclined	
weight, ready for use	lb	33.5
temperature range	°F	-4 + 131
weight excl. battery	lb	31.3
dimensions (AxBxC)	in	32.4 x 10.9 x 9.9
EN 13204 compliant	Yes	
EN 13204 classification	BC150F-15.2	
EN 13204, cutting capacity	1H 2G 3G 4F 5G	
NFPA 1936 compliant	Yes	
NFPA 1936, cutting capacity	A6 B5 C6 D6 E6	

### Safety factors / tests

hydraulic safety factor	2:1
endurance test tool	1000 cycles of biting in material that cannot be cut
endurance test dead man's handle	6000 cycles

### Standard supplied with

- Carrying handle with integrated LED lighting
- i-Bolt Technology

### Required articles

Greenline Battery BPA283	150.005.823
Greenline Battery BPA285	150.006.208
Greenline Battery Charger BCH1	150.182.208
Greenline Battery Charger BCH2	150.182.209
Greenline Battery Charger BCH3	150.182.286

### Accessories

Mains Power Connector BMC1	150.182.206
Mains Power Connector BMC2	150.182.207
Carrying Strap	150.182.249
Battery Pouch	150.182.214

