

Cutter | GCU 5060 i EVO 3 (excl. battery)

Specifications

article number	158.052.203	
model	GCU 5060 i EVO 3 (excl. battery)	
short description	Cutter	
max. working pressure	psi	10443
max. cutting opening	in	8.1
theoretical cutting force	lbf	396788
protection rate	IP54	
sound emission @ 1m/3.25ft	dB(A)	74
sound emission @ 4m/13ft	dB(A)	65
hydraulic oil type	ISO-L HV VG 15/22	
NCT	✓	
cutter jaw	inclined	
weight, ready for use	lb	56.0
temperature range	°F	-4 + 131
weight excl. battery	lb	53.8
dimensions (AxBxC)	in	37.8 x 13.5 x 11.2
EN 13204 compliant	Yes	
EN 13204 classification	CC205K-25.4	
EN 13204, cutting capacity	1K 2K 3K 4K 5K	
NFPA 1936 compliant	Yes	
NFPA 1936, cutting capacity	A9 B9 C9 D9 E9	

Safety factors / tests

hydraulic safety factor	2:1
endurance test tool	1000 cycles of biting in material that cannot be cut
endurance test dead man's handle	6000 cycles

Standard supplied with

- Carrying handle with integrated LED lighting
- i-Bolt Technology

Required articles

Greenline Battery BPA283	150.005.823
Greenline Battery BPA285	150.006.208
Greenline Battery Charger BCH1	150.182.208
Greenline Battery Charger BCH2	150.182.209
Greenline Battery Charger BCH3	150.182.286

Accessories

Mains Power Connector BMC1	150.182.206
Mains Power Connector BMC2	150.182.207
Carrying Strap	150.182.249
Battery Pouch	150.182.214

