



FD-PAA

The AttackPRO Truck Charger lets you securely mount and charge the camera and an additional battery inside the apparatus. Mount the truck charger vertically or horizontally to any suitable and stable surface to keep your AttackPRO charged and ready. Camera and batteries not included.

What's included in the box:


- Truck Charger unit
- Power supply (for AC power)
- AC plugs for US, EU, and UK (for power supply)
- Accessory Kit: Fuse holder/fuse, self-tapping mounting fastener (3x), 12/24VDC terminal connector, feet for desktop/table use (4x)
- Quick Start Guide

Equipment ratings

SPECIFICATIONS	
Supply Voltage	12VDC
Power Rating	24W
Environmental	0°C to 40°C operating, 10% - 90% RH
Dimensions	10 x 9.1 x 5 inches
Weight	~ 2lbs (0.9kg)
Charge Time (battery)	5 hours
Charge Time (camera)	5 hours

Recommended fuse and cable for hardwire install

SPECIFICATIONS	
Cable	16AWG Stranded SAE J1128
Fuse	Auto 3A 32VDC Blade mini
Environmental	Intended for indoor use only



Seek more at thermal.com

6300 Hollister Ave, Santa Barbara, CA 93117

Seek Thermal engineers, designs and manufactures high quality thermal imaging products and core platforms for consumer, commercial, and heat sensing IoT data applications. With headquarters in Santa Barbara, California, the global hub of thermal imaging innovation, the company has developed breakthrough thermal imaging camera cores that will enable a range of affordable products for use at home, work and play. For more information visit thermal.com and follow #seekthermal on Instagram and @seekthermal on Twitter.