

	CAT NO.	BATTERIES (included unless noted)	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANST LIGHT OUTPUT	ANST RUN TIME	ANST BEAM DISTANCE (meters)	ANST PEAK BEAM INTENSITY (candela)	ANST WATERPROOF/ SUBMERSIBLE/ WATER RESISTANT	APPROVALS	COLORS
5-SERIES LIGHTS	5000	2 AAA Alkaline	2.4 oz. (0.07)	5.59" (14.2)	202", 21"	1h 15m", 7h**	69", 21"	1176", 111"	IPX8	N/A	■
	5010	2 AAA Alkaline	5.1 oz. (0.15)	6.26" (15.9)	392", 22"	2h 15m", 26h**	184", 43"	8507", 452"	IPX8	N/A	■
	5020	4 AAA Alkaline	7.3 oz. (0.21)	5.87" (14.9)	586", 217", 20"	1h", 2h 30m", 27h**	250", 147", 44"	15672", 5368", 480"	IPX8	N/A	■
	5050R	1 Rechargeable Lithium-Ion	5.8 oz. (0.16)	6.16" (15.6)	393", 21", 883"	2h 30m", 40h", N/A ⁸	134", 30", 201"	4488", 224", 10093 ⁸	IPX8	N/A	■
	3310PL	3 AA Alkaline	6.2 oz. (0.18)	6.14" (15.6)	378", 39"	8h", 202h"	196", 62"	9580", 961"	IPX8	N/A	■ photoluminescent
PHOTOLUMINESCENT LIGHTS	3310ELS	3 AA Alkaline	6.2 oz. (0.18)	6.14" (15.6)	378", 39"	8h", 202h"	196", 62"	9580", 961"	IPX8	N/A	■ photoluminescent
	3410	3 AA Alkaline (Not Included)	9.2 oz. (2.61)	7.44" (18.9)	653", 97", 25"	5h", 19h", 61h"	184", 67", 34"	8504", 1129", 292"	IPX8	N/A	■ photoluminescent
	3410M	3 AAA Alkaline	3.2 oz. (0.09)	1.49" (3.8)	30", 14"	19h", 47h"	28", 19"	194", 91"	IPX4	CI D1, IECEx ia	■
	2610	3 AAA Alkaline	3.2 oz. (0.09)	1.49" (3.8)	30", 14"	19h", 47h"	28", 19"	194", 91"	IPX4	CI II III D1, IECEx ia	■
	2690	3 AAA Alkaline	4.1 oz. (0.12)	2.81" (7.1)	74	11h	92	2124	IPX7	CI II III D1, IECEx ia	■
HEADLAMPS	2720	3 AAA Alkaline	3.8 oz. (0.11)	2.48" (6.3)	200", 12"	3h", 103h"	82", 20"	1684", 103"	IPX4	N/A	■
	2740	3 AAA Alkaline	3.3 oz. (0.09)	2.25" (5.7)	66", 36"	7h 15m", 21h"	22", 16"	68"	IPX4	N/A	■
	2745	3 AAA Alkaline	3.3 oz. (0.09)	2.25" (5.7)	33", 17"	20h", 40h"	35", 25"	309", 155"	IP54	CI D1, IECEx ia	■
	2750	3 AAA Alkaline	3.4 oz. (0.1)	2.25" (5.7)	259", 71"	2h 30m", 11h"	90", 48"	2041", 573"	IPX4	N/A	■ photoluminescent
	2755	3 AAA Alkaline	3.4 oz. (0.1)	2.25" (5.7)	118", 60"	7h 30m", 16"	60", 43"	910", 454"	IP54	CI D1, IECEx ia	■
COLOR CORRECT LIGHTS	2760	3 AAA Alkaline	3.4 oz. (0.1)	2.25" (5.7)	289", 156", 97", 42"	1h 30m", 3h 15m", 5h 30m", 11h"	101", 66", 48", 19"	2540", 1097", 567", 88"	IPX4	N/A	■
	2765	3 AAA Alkaline	3.4 oz. (0.1)	2.25" (5.7)	155", 132", 78", 34"	6h 15m", 5h 30m", 8h", 14h"	81", 68", 46", 10"	1649", 1157", 529", 23"	IP54	CI D1, IECEx ia	■
	2780	4 AA Alkaline	8.8 oz. (0.25)	3" (7.6)	430", 203", 53"	1h 30m", 3h", 12h"	124", 81", 27"	3868", 1625", 425"	IPX7	N/A	■ photoluminescent
	2780R	1 Rechargeable Lithium-Ion	7.3 oz. (0.21)	3" (7.6)	558", 213", 95"	2h", 3h", 7h 30m"	127", 78", 53"	4060", 1540", 695"	IPX4	N/A	■ photoluminescent
	2785	4 AA Alkaline	8.8 oz. (0.25)	3" (7.6)	215", 106", 22"	5h", 13h", 98h"	108", 76", 34"	2911", 1445", 290"	IP54	CI D1, IECEx ia	■
REMOTE AREA LIGHTING SYSTEMS	2750CC	3 AAA Alkaline	3.4 oz. (0.1)	2.25" (5.7)	183", 50"	2h 30m", 11h"	63", 31"	989", 240"	IPX4	N/A	■ photoluminescent
	2755CC	3 AAA Alkaline	3.4 oz. (0.1)	2.25" (5.7)	72", 36"	6h 45m", 15"	50", 35"	632", 302"	IP54	CI D1, IECEx ia	■
	3310CC	3 AA Alkaline	6.2 oz. (0.18)	6.14" (15.6)	283", 31"	8h", 175h"	169", 50"	7150", 625"	IPX8	N/A	■ photoluminescent
	3315CC	3 AA Alkaline	6.2 oz. (0.18)	6.14" (15.6)	130	16h 30m	110	3042	IP67	CI II III D1, IECEx ia	■
	3410MCC	3 AA Alkaline (Not Included)	9.2 oz. (0.26)	7.44" (18.9)	484", 67", 17"	4h", 20h", 67h"	155", 56", 29"	5991", 796", 29"	IPX8	N/A	■ photoluminescent
REMOTE AREA LIGHTING SYSTEMS	3415MCC	3 AA Alkaline (Not Included)	9.0 oz. (0.25)	7.44" (18.9)	258", 127", 144"	5h", 13h", 13h"	111", 30", 109"	3109", 231", 2998"	IPX8	ETL, CI II III D1, IECEx ia	■
	CAT NO.	BATTERIES (included unless noted)	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	LUMENS	RUN TIME	BEAM SPREAD	NUMBER OF LEDs	LAMP HEADS	APPROVALS	COLORS
REMOTE AREA LIGHTING SYSTEMS	9430	Rechargeable, Sealed Lead Acid	22.65 lbs. (10.3)	32.28" (82)"	3000", 1500"	8h", 15h"	125"	6	1	N/A	■
	9430SL	Rechargeable, Sealed Lead Acid	22.05 lbs. (10)	32.28" (82)"	2000", 1000"	8h", 15h"	10"	24	1	N/A	■
	9440	Rechargeable Lithium-Ion	16.09 lbs. (7.3)	85" (215.8)"	5300", 2800", 1400"	1h 30m", 4h", 8h"	125"	12	1	N/A	■
	9455	Rechargeable NiMH	16.00 lbs. (7.3)	31.50" (80)"	1600", 800"	5h", 10h"	125"	10	1	CI D1, IECEx ia, ATEX Zone 0	■ High Visibility Yellow
	9460	Rechargeable, Sealed Lead Acid	61 lbs. (27.7)	79.50" (201.9)"	12,000 (variable)	3h", 24h"	120"	10 per head	2	N/A	■
REMOTE AREA LIGHTING SYSTEMS	9460M	Rechargeable, Sealed Lead Acid	64 lbs. (29)	79.50" (201.9)"	12,000 (variable)	3h", 24h"	120"	10 per head	2	N/A	■
	9470	Rechargeable, Sealed Lead Acid	105 lbs. (47.6)	82.00" (208.3)"	24,000 (variable)	2h 45m", 24h"	120"	10 per head	4	N/A	■
	9470M	Rechargeable, Sealed Lead Acid	108 lbs. (49)	82.00" (208.3)"	24,000 (variable)	2h 45m", 24h"	120"	10 per head	4	N/A	■
	9480	Rechargeable, Sealed Lead Acid	27.5 lbs. (12.5)	23.75" (60.3)"	4000", 3000", 1000"	6h", 8h", 28h"	125"	8	1	N/A	■
	9490	Rechargeable, Sealed Lead Acid	32 lbs. (14.5)	72" (182.9)A	6000 (variable)	3h 30m", 12h", 24h"	125"	10	1	N/A	■
REMOTE AREA LIGHTING SYSTEMS	9500	N/A	29.8 lbs. (13.5)	Case: 20.62" (52.4) Cord Length: 157.5" (4000.1)	6000 (white LED), 1200 (red LED)	constant 120V	210" (diffused)	36 per head	3	N/A	■
	9600	N/A	9.04 lbs. (4.1)	Light Head Height: 114" (289.6) Cord Length: 552" (1402.1)	3,000	constant 120V	N/A	14	1	N/A	■

*High **Medium ***Low ****Downcast ^AExtended Height ^BBoost ^FFlashing Additional safety certifications may apply. For details go to www.pelican.com



LUGGAGE



WATERTIGHT CASES



URBAN AND SPORT
BACKPACKS



BIOTHERMAL



PELICAN ELITE COOLERS



DRINKWARE

MEET THE OTHER HALF OF PELICAN

The same durability and ingenuity built into every Pelican light also sets our other products apart. We're protecting equipment around the world from the toughest environments.

FOR THE FULL LINE OF PELICAN PRODUCTS GO TO WWW.PELICAN.COM

FLASHLIGHTS/HEADLAMPS

PELICAN LIMITED LIFETIME GUARANTEE OF EXCELLENCE

Pelican Products, Inc. ("Pelican") guarantees its lights for a lifetime against breakage or defects in workmanship. This guarantee does not cover the lamp or batteries. Pelican will either repair or replace any defective product, at our sole option. All warranty claims of any nature are barred if the product has been altered, damaged or in any way physically changed, or subjected to abuse, misuse, negligence or accident. Lifetime warranty does not cover Remote Area Lighting Systems products.

In Australia: www.pelican.com/warranty/
For complete warranty details: www.pelican.com/warranty/

REMOTE AREA LIGHTING SYSTEMS

1 YEAR LIMITED WARRANTY

Pelican Products, Inc. ("Pelican") guarantees its Remote Area Lighting Systems (RALs) against defects in materials and workmanship under normal use, service, and maintenance for a period of one year from the date of purchase. With valid dated proof of purchase, Pelican will either repair or replace any defective product, at our sole option. All warranty claims of any nature are barred if the product has been altered or in any way physically changed, or subjected to abuse, misuse, negligence or accident.

In Australia: www.pelican.com/warranty/
For complete warranty details: www.pelican.com/warranty/

U.S.A.

CALIFORNIA 23215 Early Avenue Torrance, CA 90505 Tel: 310.326.4700 800.473.5422 Fax: 310.326.3311 www.pelican.com	MASSACHUSETTS 147 North Main Street South Deerfield, MA 01373 Tel: 800.542.7344 Fax: 413.665.8330 www.pelican.com	MINNESOTA Pelican BioThermal Headquarters 3020 Niagara Ln N Plymouth, MN 55447 Tel: 763.412.4800 877.537.9800 www.pelicanbiothermal.com
---	--	---


INTERNATIONAL

AUSTRALIA Pelican Products Pty Ltd West Wing, Platinum Building, Suite 2.33, 4 Ilya Av Erina NSW 2250 Tel: +612 4367 7022 Fax: +612 4367 7046 www.pelicanaustralia.com	CANADA Pelican Products ULC 10221-184th Street Edmonton, Alberta T5S 2J4 Canada Tel: +780 481 6076 Fax: +780 481 9586 www.pelican.com/ca	CHINA Pelican Products China Representative Office Pine City Building, Room 1026 777 Zhaojiabang Road Shanghai, China 200032 Tel: +86 21 64189685 Fax: +86 21 64189679 www.pelican.com/cn	EUROPE, MIDDLE EAST AND AFRICA Peli Products, S.L.U. c/ Provença, 388, Planta 7 08025 Barcelona, Spain Tel: +34 934 674 999 Fax: +34 934 877 393 www.peli.com
KOREA Pelican Products Korea Ltd #909 Hyundai 41 Tower, #2616 917-9, Mok-dong, Yangcheon-gu, Seoul, Korea 158-950 Tel: +82 2 6092 4700 Fax: +82 2 6739 4700	JAPAN Pelican Products K.K. Nisso 22 Bldg 9F 1-11-10 Azabu Dai Minato ward Tokyo 106-0041 Japan Tel: +81 33 585 9100 Fax: +81 33 585 9109 www.pelican.com/jp	LATIN AMERICA 23215 Early Avenue Torrance, California 90505 USA Tel: +1 310-326-4700 x 1462 Fax: +1 310-325-5740 www.pelican.com	SE ASIA and Rest of ASIA (Hong Kong, Macau, Taiwan, Pakistan) 19 Tukang Innovation Drive Greenhub #04-01 Singapore 618301 tel: +65 9298 3322 www.pelican.com


DISTRIBUTED BY:

Printed in the USA on FSC-Certified Paper

©2020 Pelican Products, Inc. All trademarks are registered and/or unregistered trademarks of Pelican Products, Inc., its subsidiaries and/or affiliates.
Part. No. 0030-003-600 NV/20



TOUGH LIGHTING TOOLS



SINCE 1976

SPECIFICATIONS AND FEATURES

	CAT NO.	BATTERIES (included unless noted)	WEIGHT W/ BATTERIES (KG)	LENGTH (CM)	ANSI LIGHT OUTPUT	ANSI RUN TIME	ANSI BEAM DISTANCE (meters)	ANSI PEAK BEAM INTENSITY (candela)	ANSI WATERPROOF/ SUBMERSIBLE/ WATER RESISTANT	APPROVALS	COLORS
SMALL LIGHTS	1810	4 LR 41 Alkaline	0.5 oz. (0.01)	1.5" (3.8)	16	8h 45m	23	137	IPX4	N/A	■
	1910	1 AAA Alkaline	1.5 oz. (0.04)	3.8" (9.6)	106", 21"	2h 30m", 4h"	55", 24"	765", 140"	IPX7	N/A	■
	1920	2 AAA Alkaline	2.2 oz. (0.06)	5.5" (14)	224", 22"	2h 15m", 8h 45m"	81", 25"	1640", 152"	IPX7	N/A	■
	1970	2 AAA Alkaline	1.8 oz. (0.05)	5.75" (14.6)	139	4h 15m	29	205	IPX4	N/A	■
	2130	2 L1154 Alkaline	0.5 oz. (0.01)	1.73" (4.4)	N/A	N/A	N/A	N/A	IPX7	N/A	■
	2130IR	2 L1154 Alkaline	0.5 oz. (0.01)	1.73" (4.4)	N/A	N/A	N/A	N/A	IPX7	N/A	■
	2310	2 AA Alkaline	4.6 oz. (0.13)	6.22" (15.8)	350", 25"	2h 15m", 27h"	134", 36"	4516", 324"	IPX8	N/A	■
	2365	2 AA Alkaline (Not Included)	9.3 oz. (0.26)	21.92" (55.7)	65	7h	81	1644	IPX4	N/A	■
RIGHT ANGLE SAFETY	2490	4 AA Alkaline (Not Included)	8.2 oz. (0.23)	12.5" (31.8)	64	12h	118	3459	IPX7	N/A	■
	3315R-RA	1 Rechargeable Lithium Iron Phosphate	7.1 oz. (0.2)	7.00" (17.8 cm)	132", 15"	5h", 34h"	108", 35"	2931", 308"	IP67	CI D1, IECEx ia	■
	3415	3 AA Alkaline	9 oz. (0.25)	7.44" (18.9)	336", 177", 186"	6h", 15h", 14h"	133", 37", 135"	4418", 336", 4544"	IPX8	CI II III D1, IECEx ia	■
	3610	4 AA Alkaline	10.5 oz. (0.3)	7.51" (19.1 cm)	183	5h 45m	184	8480	IPX7	CI II III D1, IECEx ia	■
	3610PL	4 AA Alkaline	10.5 oz. (0.3)	7.51" (19.1 cm)	183	5h 45m	184	8480	IPX7	CI II III D1, IECEx ia	■ ■ shroud is photoluminescent
	3715	4 AA Alkaline (Not Included)	14.4 oz. (0.41)	5.36" (13.6)	233", 113", 31"	4h", 7h", 31h"	293", 187", 30"	21440", 8775", 220"	IPX4	CI D1, IECEx ia	■
	3715PL	4 AA Alkaline (Not Included)	14.4 oz. (0.41)	5.36" (13.6)	233", 113", 31"	4h", 7h", 31h"	293", 187", 30"	21440", 8775", 220"	IPX4	CI D1, IECEx ia	■ ■ shroud is photoluminescent
	3765	4 Rechargeable Ni-MH	14.6 oz. (0.41)	5.36" (13.6)	237", 113", 32", 140"	3h", 6h 30m", 14h", 9h"	301", 193", 28", 274"	22720", 9354", 192", 18784"	IPX4	CI D1	■
	3765PL	4 Rechargeable Ni-MH	14.6 oz. (0.41)	5.36" (13.6)	237", 113", 32", 140"	3h", 6h 30m", 14h", 9h"	301", 193", 28", 274"	22720", 9354", 192", 18784"	IPX4	CI D1, CI D2	■ ■ shroud is photoluminescent
	SAFETY LIGHTS	1930	4 LR 44 Alkaline	0.9 oz. (0.03)	2.64" (6.7)	12	4h 15m	17	70	IPX4	CI D1, CI II D2, IECEx ia
2220		2 CR2032 Lithium	1 oz. (0.03)	3.5" (8.9)	9	34h	12	38	IPX4	CI D1, IECEx ib	■
1830		3 AAAA Alkaline	1.2 oz. (0.03)	6.2" (15.7)	5	32h	13	44	IPX4	CI D1, CI D2	■
1975		2 AAA Alkaline	1.9 oz. (0.05)	5.75" (14.6)	117	2h 15m	24	141	IPX4	CI II III D1	■
1975I		2 AAA Alkaline	1.9 oz. (0.05)	5.75" (14.6)	117	2h 15m	24	141	IPX4	IECEx ia	■
1965		2 AAA Alkaline	1.9 oz. (0.05)	5.88" (13.9)	87	2h 30m	41	429	IPX7	CI II III D1	■
2010		3 C Alkaline (Not Included)	13.4 oz. (0.38)	8.11" (20.6)	161	22h	160	6398	IPX7	CI II III D1, IECEx ia	■ ■
2010PL		3 C Alkaline (Not Included)	13.4 oz. (0.38)	8.11" (20.6)	161	22h	160	6398	IPX7	CI II III D1, IECEx ia	■ ■ shroud is photoluminescent
2315		2 AA Alkaline	4.6 oz. (0.13)	6.22" (15.8)	115	6h	75	1403	IPX8	CI II III D1, IECEx ia	■
2410		4 AA Alkaline	7.3 oz. (0.21)	7" (17.8)	183	5h 45m	184	8480	IPX7	CI II III D1, IECEx ia	■ ■
2410PL		4 AA Alkaline	7.3 oz. (0.21)	7" (17.8)	183	5h 45m	184	8480	IPX7	CI II III D1, IECEx ia	■ ■ shroud is photoluminescent
2460		4 Rechargeable NiMH	7.8 oz. (0.22)	7" (17.8)	183	5h	179	8050	IPX7	CI II D2	■
3315		3 AA Alkaline	6.2 oz. (0.18)	6.14" (15.6)	160	19h	144	5153	IP67	CI II III D1, IECEx ia	■
3315PL		3 AA Alkaline	6.2 oz. (0.18)	6.14" (15.6)	160	19h	144	5153	IP67	CI II III D1	■ photoluminescent
3315R		1 Rechargeable Lithium Iron Phosphate	4.6 oz. (0.13)	6.11" (15.5)	132", 15"	5h", 34h"	108", 35"	2931", 308"	IP67	CI D1, IECEx ia	■
3325		3 AA Alkaline	6.1 oz. (0.17)	6.06" (15.4)	171	16h	136	4558	IPX7	CI II III D1, IECEx ia	■
3345		3 AA Alkaline (Not Included)	7.5 oz. (0.23)	7.25 (18.4cm)	280", 117", 219"	7h", 14h", 12h"	126", 16", 137"	3990", 60", 4724"	IPX7	ETL, CI II III D1, IECEx ia	■
TACTICAL LIGHTS		9415	4 Rechargeable NiMH	49.3 oz. (1.4)	8.75" (22.2)	588", 224"	4h 30m", 11h 30m"	288", 176"	20792", 7787"	IPX4	CI D1
	9415I	4 Rechargeable NiMH	58.2 oz. (1.65)	8.75" (22.2)	392", 144"	4h 30m", 11h"	392", 234"	32767", 13747"	IPX4	IECEx ia, ATEX Zone 0	■
	2350	1 AA Alkaline	3.4 oz. (0.1)	4.23" (10.7)	178", 15"	2h 15m", 21h"	130", 37"	4196", 345"	IPX7	N/A	■
	2360	2 AA Alkaline	5.4 oz. (0.15)	6.2" (15.7)	375", 29"	2h 30m", 13h"	192", 53"	9187", 705"	IPX8	N/A	■
	2370	2 AA Alkaline	6.5 oz. (0.18)	6.43" (16.3)	358", 35"	2h", 11h"	190", 57"	9000", 823"	IPX7	N/A	■
	PM6 3330	2 CR123 Lithium	3.5 oz. (0.1)	5.27" (13.4)	90	4h 45m	88	1959	IPX4	N/A	■
	7000	2 CR123 Lithium	5.6 oz. (0.16)	5.31" (13.5)	774", 457", 99"	1h 15m", 1h 45m", 13h"	246", 176", 138"	14768", 7712", 1738"	IPX7	N/A	■
	7060	1 Rechargeable Lithium-Ion	10.4 oz. (0.3)	8.65" (22)	535", 218", 26"	3h 45m", 12h", 68h"	207", 131", 44"	10707", 4297", 481"	IPX4	N/A	■
	7070R	1 Rechargeable Lithium-Ion	7.9 oz. (0.22)	6.88" (17.5)	1219", 626", 32"	2h 15m", 4h 15m", 32h"	235", 168", 40"	13872", 7066", 400"	IPX8	N/A	■
	7100	1 Rechargeable Lithium-Ion	4.4 oz. (0.13)	5.12" (13)	695", 348", 33"	1h 15m", 1h 30m", 9h 15m"	194", 130", 38"	9314", 4247", 358"	IPX8	N/A	■
	7110	1 AA Alkaline	4.1 oz. (0.12)	4.63" (11.8)	445", 214", 23"	1h", 1h 30m", 13h"	93", 62", 20"	6053", 2695", 288"	IPX8	N/A	■
	7600	1 Rechargeable Lithium-Ion	6.9 oz. (0.20)	6.19" (15.7)	944", 479", 37"	3h 15m", 4h 30m", 29h"	225", 157", 44"	12693", 6172", 480"	IPX8	N/A	■
7610	1 AA Alkaline	5.5 oz. (0.16)	5.44" (13.8)	1018, 531", 25"	1h 30m", 2h", 33h"	227", 151", 33"	12856", 5674", 273"	IPX8	N/A	■	
7620	2 AA Alkaline	6.9 oz. (0.20)	6.75" (17.1)	1124", 528", 28"	2h", 3h", 37h"	243", 155", 35"	14824", 5974", 315"	IPX8	N/A	■	
8060	4 Rechargeable NiMH	23.2 oz. (0.66)	12.67" (32.2)	1072", 551", 29"	3h 45m", 4h 15m", 60h"	376", 265", 60"	35300", 17520", 889"	IPX6	N/A	■	
9410L	6 Rechargeable Lithium-Ion	44.7 oz. (1.27)	8.75" (22.2)	2207", 463"	3h 15m", 11h"	453", 207"	51304", 10710"	IPX4	N/A	■ ■	

SMALL LIGHTS

1810

1910

1920

1970

2130

2130IR

2310

NEW

2365

2490

Snap-On magnetic base

Traffic Wand Included

5-SERIES LIGHTS

5000

5010

5020

5050R

PHOTOLUMINESCENT LIGHTS

3310PL

3310ELS

3410/3410M

3410M Includes Magnetic Clip

RIGHT ANGLE SAFETY

SAFETY CERTIFIED

3315R-RA

3415/3415M

3610

3715

3765

3415M Includes Magnetic Clip

Photoluminescent Shroud Available
3610PL
3715PL
3765PL

COLOR CORRECT LIGHTS

2750CC

2755CC

3310CC

3315CC

3410MCC

3415MCC

SAFETY LIGHTS

SAFETY CERTIFIED

1930

2220

1830

1975

1975i

1965

2010 / 2010PL

2315

NEW

2410 / 2410PL

Photoluminescent Shroud Available

Photoluminescent Shroud Available

2460

3315

3315PL

3315R

3325

3345

9415

9415i

TACTICAL LIGHTS

2350 / 2350COMBO

2360

2370

PM6 3330

7000

7060

7070R

Combo Includes Helmet Mount

7100

7110

7600

7610

7620

8060

9410L

Optional

Optional

LEGEND

Optional Wand and Holster Available

Optional Holster Available

Optional Holster and Helmet Mount Available

Optional Helmet Mount Available

Rechargeable

WARNING: This product can expose you to chemicals including Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov

REMOTE AREA LIGHTING SYSTEMS

9430

9430SL

9455

9480

9490

9440

9460/9460M

9470/9470M

9600

9500

Shown with base & pole accessories
Non-Rechargeable

Mobility Version Shown

Non-Rechargeable

HEADLAMPS

2720

2740

2750

2760

2780

2780R

HeadsUp Lite™ 2610

HeadsUp Lite™ 2690

2745

2755

2765

2785